

# MATERIAL SAFETY DATA SHEET

## PRODUCT IDENTIFICATION

Trade Name (as labeled) Latex Glue, Acrylic Glue  
Manufacturers Name Orco Blended Products  
Complete Mailing Address 27347 3<sup>rd</sup>. Street, Highland, CA 92346  
Phone Number 1-877-838-6726

Date prepared or revised  
June 29, 1999

## HAZARDOUS INGREDIENTS

Chemical Names	CAS Numbers	Percent*	Exposure Limits in Air (give units)
			ACGIH TLV OSHA PEL

As we interpret the Occupational Safety and Health Act of 1970, This products should not be considered hazardous.

## PHYSICAL PROPERTIES

Vapor Density (air=1)	N/A	Melting Point or Range	212 F
Specific Gravity	1.01	Boiling Point or Range	N/A
Solubility in Water	< .1%	Evaporation Rate (butyl acetate = 1)	
Vapor Pressure, mmHg at 20 deg C	N/A		
Appearance and odor	Milky White liquid with slight ammonia odor		

**HOW TO DETECT THIS SUBSTANCE\*** (warning prope rties of substance as a gas, vapor, dust, or mist)

---

\*Not a required Category.

**NOTE: All required categories should be addressed. If any item is not applicable, or no information is available, the space must be marked to indicate that.**

## FIRE AND EXPLOSION

Flash Point deg F ( give method) Non Combustible and non explosive  
Auto ignition temperature deg F N/A  
Flammable limits in air, volume % None lower(LEL) None upper (UEL) None  
Fire Extinguishing materials:  
\_\_\_\_\_ water spray \_\_\_\_\_ carbon dioxide \_\_X\_\_ other Dry Resin ONLY/water fog  
\_\_\_\_\_ foam \_\_\_\_\_ dry chemical

Special firefighting procedures: None

Unusual fire and explosion hazards: Burned, dry resin emits dense, black smoke. Non explosive.

## HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

**Inhaled :** None

**Contact with skin or eyes:** Minor irritation upon contact

**Absorbed through skin :** N/A

**Swallowed :** Low single dosage toxicity

---

HEALTH EFFECTS OR RISKS FROM EXPOSURE. Explain in lay terms. Attach extra page if more space is needed.

**Acute:** Minor irritation may occur to the eyes and skin

**Chronic:** None.

---

FIRST AID: EMERGENCY PROCEDURES

**Eye Contact:** Wash eyes immediately with running water for 15 minutes, including under eyelids. Get prompt medical attention.

**Skin Contact:** Wash exposed area with large amounts of soap and water. Remove and wash contaminated clothing. Apply skin lotion.

**Swallowed:** Low in toxicity. Induce vomiting if large amounts are ingested.

---

SUSPECTED CANCER AGENT

\_\_X\_\_ NO: This products ingredients are not found in the lists below

Not as a carcinogen

\_\_\_\_\_ YES \_\_no\_\_ NTP \_\_yes\_\_ IARC Class 2A. IARC monographs on the evaluation of the carcinogenic risk of chemicals to humans (volume 42, 198) concludes that there is sufficient evidence for the carcinogenicity of crystalline silica to experimental animals and that there is limited evidence of the carcinogenicity of crystalline silica to humans.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Pulmonary function may be reduced by inhalation of respirable crystalline silica. Also, lung scarring produced by such inhalation may lead to a progressive massive fibrosis of the lung, which may aggravate other pulmonary conditions, and diseases which increase susceptibility to pulmonary tuberculosis.

---

## REACTIVITY DATA

Stability \_\_X\_\_ Stable – keep dry until used \_\_\_\_\_ Unstable

**Conditions to avoid:** None

**Incompatibility (materials to avoid):** Contact with oxidizing agents such as: Fluorine, Chlorine Trifluorine, Manganese Trioxide, Oxygen Difluoride, may cause fires. Also avoid Ammonium Salts, Phosphorus and organic compounds.

**Hazardous decomposition products (including combustion products):** Silica will dissolve in Hydrofluoric Acid and produce a corrosive gas - Silicon Tetrafluoride.

Hazardous polymerization: \_\_\_\_\_ may occur        X   will not occur

Conditions to avoid: Handling procedures, which may generate dust. Contact with Nitroparaffins, Maleic Anhydride or phosphorone.

---

### **SPILL, LEAK AND DISPOSAL PROCEDURES**

**Spill response procedures (include employee protection measures):** Use dry clean up methods that do not disperse the dust into the air. Avoid breathing the dust. Emergency procedures are not required. Wear protective equipment specified below.

**Preparing wastes for disposal (container types, neutralization, etc.):** Small amounts of material can be disposed of as common waste or returned to the container for later use if it is not contaminated. Large volumes may require special handling.

**NOTE:** Dispose of all wastes in accordance with federal, state and local regulations.

---

### **SPECIAL HANDLING INFORMATION**

**Ventilation and engineering controls:** Use sufficient local exhaust to reduce the level of respirable crystalline silica to the PEL. See ACGIH Industrial Ventilation, a manual of recommended practices.

**Respiratory protection (type):** Industry environments, the use of a OSHA/NIOSH approved respirator is recommended.

**Eye Protection (type):** Use tight fitting goggles industry environments. An eyewash station should be readily available.

**Gloves (specific material):** Abrasion and alkali resistant rubber gloves.

**Other clothing and equipment:** Protective clothing to protect the skin from prolonged contact with the wet mortar.

**Work practices, hygienic practices:** Workers should shower with soap and water immediately after handling materials.

**Other handling and storage requirements:** Avoid generating dust. Keep material dry. Avoid contact with incompatible materials.

### **PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT**